

TG20/3 IP44

ZAPFWELLENGENERATOR



Diese Generatoren bieten viele Möglichkeiten der Stromversorgung für alle landwirtschaftlichen Betriebe.

Leistung

Drei Phasen Leistung COP	kVA	18
Einphasig Leistungs COP	kVA	9

Spezifikationen

Spannung	V	400/230
Frequenz	Hz	50
Leistungsfaktor	cos ϕ	0.8/1
Umdrehungen Zapfwelle	U/min	3000
Power (tractor)	kW/HP	37/50
Umdrehungen Zapfwelle	U/min	435
Über- Unterspannungsrelais	%	5



Maßangaben

Länge	(L) mm	958
Breite	(W) mm	645
Höhe	(H) mm	1003
Leergewicht	Kg	160

Ausstattungen

Thermomagnetic circuit breaker	x
FI-Schutzschalter	x
Spannungsmesser	x
Frequenzzähler	x
Min - max Voltage controller	x

Steckdosen

SCHUKO 230V 16A IP54	1
2P+T CEE 230V 32A IP44	1
3P+N+T CEE 400V 32A IP44	1

Generator- und Steckdosenschutz

Elektro Schutz	IP44
Steckdosenschutz	IP54



The information is aligned with the Data file at the time of download. Printed on 20/11/2023 (ID 2326)

©2023 | PR Industrial S.r.l unipersonale – Loc. Il Piano – 53031 Casole d'Elsa (SI) – ITALY. Company subject to the management and coordination of Generac Power Systems Inc. | All rights reserved | Image shown may not reflect actual package. Specifications subject to change without notice

