

# TG72/15 IP44

## ZAPFWELLENGENERATOR



Diese Generatoren bieten viele Möglichkeiten der Stromversorgung für alle landwirtschaftlichen Betriebe.

### Leistung

Drei Phasen Leistung COP	kVA	64.8
Einphasig Leistungs COP	kVA	22.7

### Spezifikationen

Spannung	V	400/230
Frequenz	Hz	50
Leistungsfaktor	cos $\phi$	0.8/1
Umdrehungen Zapfwelle	U/min	1500
Power (tractor)	kW/HP	118/160
Umdrehungen Zapfwelle	U/min	395
Über- Unterspannungsrelais	%	0.5



## Maßangaben

Länge	(L) mm	1110
Breite	(W) mm	720
Höhe	(H) mm	1322
Leergewicht	Kg	470

## Ausstattungen

Thermomagnetic circuit breaker	X
FI-Schutzschalter	X
Spannungsmesser	X
Frequenzzähler	X
Min - max Voltage controller	X

## Steckdosen

SCHUKO 230V 16A IP54	1
3P+N+T CEE 400V 63A	1
CEE 400V 125A	1

## Generator- und Steckdosenschutz

Elektro Schutz	IP44
Steckdosenschutz	IP54



The information is aligned with the Data file at the time of download. Printed on 20/11/2023 (ID 2341)

©2023 | PR Industrial S.r.l unipersonale – Loc. Il Piano – 53031 Casole d'Elsa (SI) – ITALY. Company subject to the management and coordination of Generac Power Systems Inc. | All rights reserved | Image shown may not reflect actual package. Specifications subject to change without notice

